

abitex

abitex srl
via del cristo 84
33044 manzano
ud - italy

t +39 0432 746060
www.abitex.eu
info@abitex.eu

luci a san siro stripe 09005



IT

codice doganale

58013700.

utilizzo

imbottiti.

caratteristiche

58% viscosa - 14% poliestere - 28% resina,
altezza cm \pm 140, peso \pm 565 gr/m².

tintura

il prodotto è tinta in filo.

rapporto disegno

trama 17,5 cm.

lunghezza pezze

circa 25 mtl.

abrasione

>50.000 cicli, ISO 12947-2.

solidità alla luce

4/5, ISO 105 B02.

solidità allo sfregamento

secco 4, umido 3/4, ISO 105 X12.

resistenza alla cucitura

ordito 1200 N, trama 900 N, ISO 13934-2.

pilling

4/5, ISO 12945-2.

resistenza al fuoco

1IM - UNI 9175; EN 1021 1/2; BS 5852 part 1;

BS 5852 crib 5; California TB 117-2013;

IMO FTP Code 307 part 8.

attenzione

sono ammesse leggere differenze di colore tra differenti partite.

EN

customs code

58013700.

use

upholstered furniture.

features

58% viscose - 14% polyester - 28% resin, width cm \pm 140,
weight \pm 565 g/m².

dyeing

yarn dyed product.

pattern

weft 17,5 cm.

roll length

approx. 25 Im.

abrasion resistance

>50.000 rubs, ISO 12947-2.

colour fastness to light

4/5, ISO 105 B02.

fastness to rubbing

dry 4, wet 3/4, ISO 105 X12.

seam slippage

warp 1200 N, weft 900 N, ISO 13934-2.

pilling

4/5, ISO 12945-2.

fire resistance

1IM - UNI 9175; EN 1021 1/2; BS 5852 part 1;

BS 5852 crib 5; California TB 117-2013;

IMO FTP Code 307 part 8.

attenzione

slight colour differences between different batches are allowed.



fireproof



imo-med